

IZJAVA O SVOJSTVIMA  
DoP-br. MKT-231 - hr

1. Jedinствena identifikacijska oznaka vrste proizvoda: **MKT udarna tipla s unutarnjim navojem E / ES**
2. Tip, serija ili serijski broj ili bilo koji drugi element kojim se omogućuje identifikacija građevnog proizvoda, kako je potrebno sukladno članku 11. stavku 4.:  
**ETA-02/0020, dodatak A3**  
**Broj proizvodne serije: pogledajte pakiranje**
3. Namjeravana uporaba ili uporabe građevnog proizvoda, u skladu s primjenjivim usklađenim tehničkim specifikacijama, kako je predvidio proizvođač:

<b>Vrsta proizvoda</b>	razuporna tipla
<b>Za uporabu u</b>	nenapuknuti beton C20/25 - C50/60 (EN 206)
<b>Izbor</b>	7
<b>Opterećenje</b>	statički i kvazi-statički
<b>Materijal</b>	<p><u>Pocinčani čelik:</u> samo u suhim interijerima važeće dimenzije: E/ES M6x30, E/ES M8x30, E/ES M8x40, ES M10x30, E/ES M10x40, E/ES M12x50, E/ES M12x80, E/ES M16x65, E/ES M16x80, E M20x80</p> <p><u>Nehrđajući čelik (oznaka A4)</u> u unutarnjim i vanjskim prostorima, bez posebno agresivnim uvjetima važeće dimenzije: E/ES M6x30, E/ES M8x30, E/ES M8x40, E/ES M10x40, E/ES M12x50, E/ES M12x80, E/ES M16x65, E/ES M16x80, E M20x80</p> <p><u>Vrlo otporno na koroziju (oznaka HCR)</u> u unutarnjim i vanjskim prostorima s posebno agresivnim uvjetima važeće dimenzije: E/ES M6x30, E/ES M8x30, E/ES M8x40, E/ES M10x40, E/ES M12x50, E/ES M12x80, E/ES M16x65, E/ES M16x80, E M20x80</p>
<b>Raspon temperature (možda)</b>	--

4. Ime, registrirani trgovački naziv ili registrirani žig i kontaktna adresa proizvođača, kako je potrebno sukladno članku 11. stavku 5.:

**MKT Metall-Kunststoff-Technik GmbH & Co. KG**  
**Auf dem Immel 2**  
**D - 67685 Weilerbach**

5. Prema potrebi, ime i kontaktna adresa ovlaštenog predstavnika čije ovlaštenje obuhvaća zadatke poblje označene u članku 12. stavku 2.: --
6. Sustav ili sustavi ocjenjivanja i provjere stalnosti svojstava građevnog proizvoda, kako je utvrđeno u Prilogu V.:  
**Sustav 1**
7. U slučaju Izjave o svojstvima u vezi s građevnim proizvodom obuhvaćenim usklađenom normom:  
--

8. U slučaju izjave o svojstvima koja se odnosi na građevni proizvod za koji je izdana europska tehnička ocjena:

**Deutsches Institut für Bautechnik, Berlin**

izdan:

**ETA-02/0020**

na temelju

**ETAG 001-4**

Ovlaštena kuća izdaje: 1343-CPR rema sustavu 1:

- i) utvrđivanja vrste proizvoda na temelju ispitivanja tipa (uključujući uzorkovanje), izračuna tipa, tabličnih vrijednosti ili opisne dokumentacije proizvoda;
- ii) početnu inspekciju proizvodnog pogona i kontrolu tvorničke proizvodnje;
- iii) stalni nadzor, ocjenjivanje i vrednovanje kontrole tvorničke proizvodnje.

i izdano:      Certifikat o stalnosti svojstava 1343-CPR-M 550-2

9. Objavljeno svojstvo:

Bitne značajke	Metoda	Svojstva	Usklađena tehnička specifikacija
Karakteristična otpornost na vlačne sile	ETAG 001, Dodatak C	ETA-02/0020, Dodatak C1-C2	ETAG 001
	CEN/TS 1992-4		
Karakteristična otpornost sile na odrez	ETAG 001, Dodatak C	ETA-02/0020, Dodatak C3-C4	
	CEN/TS 1992-4		
Pomak u korištenju	ETAG 001, Dodatak C	ETA-02/0020, Dodatak C5	
	CEN/TS 1992-4		

U slučaju kada je sukladno članku 37. ili 38. upotrijebljena specifična tehnička dokumentacija, zahtjevi s kojima je proizvod usklađen:      --

10. Svojstvo proizvoda utvrđeno u točkama 1. i 2. u skladu je s objavljenim svojstvom u točki 9.

Ova izjava o svojstvima objavljena je pod isključivom odgovornošću proizvođača identificiranog u točki 4.

Za proizvođača i u njegovo ime potpisao:

  
**Lore Weustenhagen**  
(Managing Director)  
Weilerbach, 23.12.2014

i.V.   
**Dipl.-Ing. Detlef Bigalke**  
(Head of Product Development)



**Table C1: Characteristic values for tension loads, zinc plated steel**  
(Design method A according to ETAG 001, Annex C or CEN/TS 1992-4)

Anchor size			M6x30 <sup>1)</sup>	M8x30 <sup>1)</sup>	M8x40	M10x30 <sup>1)</sup>	M10x40	M12x50 M12x80	M16x65 M16x80	M20x80	
Installation safety factor	$\gamma_2$	[-]	1,2								
<b>Steel failure</b>											
Characteristic resistance Steel 4.6	$N_{Rk,s}$	[kN]	8,0	14,6		23,2		33,7	62,8	98,0	
Partial safety factor	$\gamma_{Ms}$	[-]	2,0								
Characteristic resistance Steel 5.6	$N_{Rk,s}$	[kN]	10,0	18,3		18,0	20,2	42,1	78,3	122,4	
Partial safety factor	$\gamma_{Ms}$	[-]	2,0			1,5		2,0			
Characteristic resistance Steel 5.8	$N_{Rk,s}$	[kN]	10,0	17,6	18,3	18,0	20,2	42,1	67,1	106,4	
Partial safety factor	$\gamma_{Ms}$	[-]	1,5						1,6		
Characteristic resistance Steel 8.8	$N_{Rk,s}$	[kN]	15,0	17,6	19,9	18,0	20,2	43,0	67,1	106,4	
Partial safety factor	$\gamma_{Ms}$	[-]	1,5						1,6		
<b>Pull-out failure</b>											
Characteristic resistance in concrete C20/25	$N_{Rk,p}$	[kN]	2)	2)	9	2)	2)	2)	2)	2)	
Increasing factor for $N_{Rk,p}$	$\psi_C$	[-]	$\left(\frac{f_{ck,cube}}{25}\right)^{0,3}$								
<b>Concrete cone failure and splitting</b>											
Effective anchorage depth	$h_{ef}$	[mm]	30	30	40	30	40	50	65	80	
Spacing (edge distance)	$s_{cr,N} (= 2 C_{cr,N})$	[mm]	3 $h_{ef}$								
	$s_{cr,sp} (= 2 C_{cr,sp})$	[mm]	190	190	190	230	270	330	400	520	
Factor for non-cracked concrete	$k_{ucr}$	[-]	10,1								

<sup>1)</sup> Use restricted to anchoring of structural components statically indeterminate and in dry interior conditions

<sup>2)</sup> Pull-out is not decisive

### Drop-in Anchor E / ES

#### Performance

Characteristic values for **tension loads, zinc plated steel**  
(Design method A according to ETAG 001, Annex C or CEN/TS 1992-4)

**Annex C1**

**Table C2: Characteristic values for tension loads, stainless steel A4, HCR**  
(Design method A according to ETAG 001, Annex C or CEN/TS 1992-4)

Anchor size			M6x30 <sup>1)</sup>	M8x30 <sup>1)</sup>	M8x40	M10x40	M12x50 M12x80	M16x65 M16x80	M20x80
Installation safety factor	$\gamma_2$	[-]	1,0						
<b>Steel failure</b>									
Characteristic resistance (property class 70)	$N_{Rk,s}$	[kN]	14,1	23,3		29,4	50,2	83,8	133,0
Characteristic resistance (property class 80)	$N_{Rk,s}$	[kN]	17,5	23,3		29,4	50,2	83,8	133,0
Partial safety factor	$\gamma_{Ms}$	[-]	1,87						
<b>Pull-out failure</b>									
Characteristic resistance in concrete C20/25	$N_{Rk,p}$	[kN]	2)	2)	9	2)	2)	2)	2)
Increasing factor for $N_{Rk,p}$	$\psi/C$	[-]	$\left(\frac{f_{ck,cube}}{25}\right)^{0,5}$						
<b>Concrete cone failure and splitting</b>									
Effective anchorage depth	$h_{ef}$	[mm]	30 <sup>3)</sup>	30	40	40	50	65	80
Spacing (edge distance)	$s_{cr,N} (= 2 C_{cr,N})$	[mm]	3 $h_{ef}$						
	$s_{cr,sp} (= 2 C_{cr,sp})$	[mm]	160	190	190	270	330	400	520
Factor for non-cracked concrete	$k_{ucr}$	[-]	10,1						

<sup>1)</sup> Use restricted to anchoring of structural components statically indeterminate and in dry interior conditions

<sup>2)</sup> Pull-out is not decisive

<sup>3)</sup> For proof against concrete cone failure as per ETAG 001, annex C or CEN/TS 1992-4-4,  $N_{Rk,c}$  must be multiplied by the factor  $(25/f_{ck,cube})^{0,2}$ .

### Drop-in Anchor E / ES

#### Performance

Characteristic values for **tension loads, stainless steel A4, HCR**  
(Design method A according to ETAG 001, Annex C or CEN/TS 1992-4)

**Annex C2**

**Table C3: Characteristic values for shear loads, zinc plated steel**  
(Design method A according to ETAG 001, Annex C or CEN/TS 1992-4)

Anchor size		M6x30	M8x30	M8x40	M10x30	M10x40	M12x50 M12x80	M16x65 M16x80	M20x80
<b>Steel failure without lever arm</b>									
Characteristic resistance Steel 4.6	$V_{Rk,s}$ [kN]	4,0	7,3	11,6	9,6	16,8	31,3	49,0	
Partial safety factor	$\gamma_{Ms}$ [-]	1,67							
Characteristic resistance Steel 5.6	$V_{Rk,s}$ [kN]	5,0	9,1	10,1	9,6	21,1	39,2	61,2	
Partial safety factor	$\gamma_{Ms}$ [-]	1,67		1,25	1,67				
Characteristic resistance Steel 5.8	$V_{Rk,s}$ [kN]	5,0	6,9	10,1	7,2	21,1	33,5	53,2	
Partial safety factor	$\gamma_{Ms}$ [-]	1,25						1,33	
Characteristic resistance Steel 8.8	$V_{Rk,s}$ [kN]	5,0	6,9	10,1	7,2	21,5	33,5	53,2	
Partial safety factor	$\gamma_{Ms}$ [-]	1,25						1,33	
Factor of ductility	$k_2$ [-]	1,0							
<b>Steel failure with lever arm</b>									
Characteristic resistance Steel 4.6	$M^0_{Rk,s}$ [Nm]	6,1	15	30	30	52	133	259	
Partial safety factor	$\gamma_{Ms}$ [-]	1,67							
Characteristic resistance Steel 5.6	$M^0_{Rk,s}$ [Nm]	7,6	19	37	37	65	166	324	
Partial safety factor	$\gamma_{Ms}$ [-]	1,67							
Characteristic resistance Steel 5.8	$M^0_{Rk,s}$ [Nm]	7,6	19	37	37	65	166	324	
Partial safety factor	$\gamma_{Ms}$ [-]	1,25							
Characteristic resistance Steel 8.8	$M^0_{Rk,s}$ [Nm]	12	30	59	60	105	266	519	
Partial safety factor	$\gamma_{Ms}$ [-]	1,25							
Factor of ductility	$k_2$ [-]	1,0							
<b>Concrete pry-out failure</b>									
k-factor	$k_{(3)}$ [-]	1,0					1,5	2,0	
<b>Concrete edge failure</b>									
Effective length of anchor under shear loading	$l_f$ [mm]	30	30	40	30	40	50	65	80
Outside diameter of anchor	$d_{nom}$ [mm]	8	10	10	12	12	15	20	25

**Drop-in Anchor E / ES**

**Performance**

Characteristic values for **shear loads, zinc plated steel**  
(Design method A according to ETAG 001, Annex C or CEN/TS 1992-4)

**Annex C3**

**Table C4: Characteristic values for shear loads, stainless steel A4, HCR**  
(Design method A according to ETAG 001, Annex C or CEN/TS 1992-4)

Anchor size		M6x30	M8x30	M8x40	M10x40	M12x50 M12x80	M16x65 M16x80	M20x80
<b>Steel failure without lever arm</b>								
Characteristic resistance (property class 70)	$V_{Rk,s}$ [kN]	7,0	10,6		13,4	25,1	41,9	66,5
Characteristic resistance (property class 80)	$V_{Rk,s}$ [kN]	8,7	10,6		13,4	25,1	41,9	66,5
Partial safety factor	$\gamma_{Ms}$ [-]	1,56						
Factor of ductility	$k_2$ [-]	1,0						
<b>Steel failure with lever arm</b>								
Characteristic resistance (property class 70)	$M^0_{Rk,s}$ [Nm]	11	26		52	92	233	454
Partial safety factor	$\gamma_{Ms}$ [-]	1,56						
Characteristic resistance (property class 80)	$M^0_{Rk,s}$ [Nm]	12	30		60	105	266	519
Partial safety factor	$\gamma_{Ms}$ [-]	1,33						
Factor of ductility	$k_2$ [-]	1,0						
<b>Concrete pry-out failure</b>								
k-factor	$k_{(3)}$ [-]	1,0	1,7		1,7		2,0	
<b>Concrete edge failure</b>								
Effective length of anchor under shear loading	$l_f$ [mm]	30	30	40	40	50	65	80
Outside diameter of anchor	$d_{nom}$ [mm]	8	10	10	12	15	20	25

**Drop-in Anchor E / ES**

**Performance**

Characteristic values for **shear loads, stainless steel A4, HCR**  
(Design method A according to ETAG 001, Annex C or CEN/TS 1992-4)

**Annex C4**

**Table C5: Displacements under tension loads**

Anchor size			M6x30	M8x30	M8x40	M10x30	M10x40	M12x50 M12x80	M16x65 M16x80	M20x80
<b>Steel zinc plated</b>										
Tension load in non-cracked concrete	N	[kN]	3	3	3,6	3,3	4,8	6,4	10	14,8
Displacement	$\delta_{N0}$	[mm]	0,24							
	$\delta_{N\infty}$	[mm]	0,36							
<b>Stainless steel A4 / HCR</b>										
Tension load in non-cracked concrete	N	[kN]	4	4	4,3	-	6,1	8,5	12,6	17,2
Displacement	$\delta_{N0}$	[mm]	0,12							
	$\delta_{N\infty}$	[mm]	0,24							

**Table C6: Displacements under shear loads**

Anchor size			M6x30	M8x30	M8x40	M10x30	M10x40	M12x50 M12x80	M16x65 M16x80	M20x80
<b>Steel zinc plated</b>										
Shear load in non-cracked concrete	V	[kN]	2	4	4	5,7	4,0	11,3	18,8	32,2
Displacement	$\delta_{V0}$	[mm]	0,9	0,9	1,0	1,5	0,6	1,2	1,2	1,6
	$\delta_{V\infty}$	[mm]	1,3	1,3	1,5	2,3	0,9	1,9	1,9	2,4
<b>Stainless steel A4 / HCR</b>										
Shear load in non-cracked concrete	V	[kN]	3,5	5,2	5,2	-	6,5	11,5	19,2	30,4
Displacement	$\delta_{V0}$	[mm]	1,9	1,1	0,7	-	1,0	1,7	2,4	2,6
	$\delta_{V\infty}$	[mm]	2,8	1,6	1,0	-	1,5	2,6	3,6	3,8

**Drop-in Anchor E / ES**

Performance  
Displacements

**Annex C5**